



KEYED NOTES:

- ① SEE MCPWSS CH. 7 FOR SIDEWALK WIDTH & THICKNESS REQUIREMENTS
- ② BASE COURSE. SEE CITY OF MISSOULA MODIFICATIONS TO MPWSS SECTIONS 02235 AND 02529
- ③ SUBGRADE. SEE CITY OF MISSOULA MODIFICATION TO MPWSS SECTION 02230
- ④ SHOULDER. SEE CITY OF MISSOULA MODIFICATION TO MPWSS SECTION 02529

GENERAL NOTES:

1. "A" TYPE MAY ONLY BE UTILIZED IN REPLACEMENT SITUATIONS AND NOT WHERE NEW CURB/SIDEWALK IS BEING INSTALLED
2. INSTALL ISOLATION JOINTS WITHIN SIDEWALK AROUND SURFACE OBJECTS WITHIN OR PROTRUDING WITHIN SIDEWALK (E.G. AROUND MANHOLES LIDS, VALVE BOXES, UTILITY POLES, HYDRANTS, POLE BASES, ETC.)
3. FOR EXPANSION AND CONTRACTION JOINTS, SEE CITY OF MISSOULA MODIFICATION TO MPWSS SECTION 02529



Engineering Division

Typical "A" Type Curb and Sidewalk Replacement Section

Approved By
City Engineer
Kevin J. Slovarp

Adopted: 04/09/1973
Revised: 01/01/2023

STD - 742