


SECTION A-A



SECTION B-B

MAINTAIN CONCRETE APRON BASE GRADE THROUGH FLARES (TYP)

GENERAL NOTES:

1. FOR REQUIREMENTS RELATED TO APPROACH WIDTH, THICKNESS, AND JOINTING, SEE MCPWSS CH. 7
2. FOR BASE, SUBBASE, AND SUBGRADE COURSE REQUIREMENTS SEE MCPWSS CH. 7 AND CITY OF MISSOULA MODIFICATION TO MPWSS SECTION 02529
3. FOR CURB CUT REQUIREMENTS SEE CITY OF MISSOULA MODIFICATION TO MPWSS SECTION 02528
4. APRON AND SIDEWALK MUST BE POURED SEPARATELY
5. SEE STANDARD DRAWING STD-772 FOR ALTERNATIVE (CURBSIDE) SIDEWALK/DRIVEWAY ADA REQUIREMENTS THROUGH DRIVEWAY
6. FOR EXISTING BOULEVARD RETROFIT, NEW SIDEWALK REPLACEMENT SECTION SHALL EXTEND TO NEAREST FULL SIDEWALK PANELS.



Engineering Division

**Standard Approach for Boulevard Sidewalk
(Less than 25 Parking Spaces)**

Approved By
City Engineer
Kevin J. Slovarp

Adopted: 04/09/1973
Revised: 01/01/2023

STD - 771